Fast Pack - Valve/Actuator Packages



Series 79 A-A/Type 57 Butterfly Standard Features (Sizes 1-1/2" - 8")

- Type-57 PVC body, PP disc, EDPM or FKM seals, wafer style
- Glass filled polyamide actuator body w/ SS trim
 1-1/2" 6" Butterfly Valves
- Aluminum body with 3-stage coating size 8"
- Rack and pinion with dual opposed piston design
- Double-acting air to OPEN / air to CLOSE
- Namur mount design for solenoid and limit switch mounting
- 80 psi supply air requirement
- Visual position indicator
- PPG Mounting bracket with 304 SS coupling and hardware
- 304 SS mounting bracket, coupling and hardware butterfly valves size 8"
- Complete factory assembled and tested actuated valve package



Series 79 A-A/Type 21 Ball Valve Standard Features (Sizes 1/2" - 4")

- Type-21 PVC with EPDM or FKM seals Tru-Union Ball Valve
- T-21 1/2" 2" supplied with both socket and threaded ends, 2-1/2" 4" socket only
- Glass filled polyamide actuator body w/ SS trim
- Rack and pinion with dual opposed piston design
- Double-acting air to OPEN / air to CLOSE
- Namur mount design for solenoid and limit switch mounting
- 80 psi supply air requirement
- Visual position indicator
- PPG Mounting bracket with 304 SS coupling and hardware
- Complete factory assembled and tested actuated valve package

| Valve Type | Size | Actuation Model |
|---------------|-----------------|-----------------|
| T-21 | 1/2" - 2" | AP79PN |
| T-21 | 2-1/2" - 4" | CP79PN |
| T-57 | 1-1/2" - 2-1/2" | BP79PN |
| T-57 | 3" - 4" | CP79PN |
| T-57 | 6" | DP79PN |
| T-57 | 8" | E79PAN |