

Fast Pack - Valve/Actuator Packages

SHIPS IN
24 HRS !



Series 92/Type 57 Butterfly Valve Standard Features (Sizes 1-1/2" - 8")

- UL-508 Listed electric actuator
- Type-57 PVC body, PP disc, EDPM or FKM seals, wafer style
- 120 VAC capacitor run reversing type motor
- Thermal overload protection with auto reset
- De-clutchable manual override
- Visual beacon position indicator
- 10 Second cycle time 1-1/2" - 4", 25 second cycle time 6" & 8" T-57 *
- Mechanical brake supplied as standard for 6" and 8" T-57
- Type 4X/7 diecast aluminum w/ powdercoat finish enclosure
- 2 End of travel limit switches
- 2 Additional limit switches for indication
- PPG mounting bracket with 304 SS coupling and hardware 304 SS mounting bracket, coupling and hardware sizes 6" & 8"
- Complete factory assembled and tested actuated valve package

*Cycle times approximate

Valve Type	Size	Actuation Model	Input Voltage	L.R. Amps	Duty Cycle
T-21	1/2" - 3"	S92M2XWJ	115 vac	0.5	100%
T-21	4"	A92M2XWJ	115 vac	0.8	75%
T-57	1-1/2" - 4"	S92M2XWJ	115 vac	0.5	100%
T-57	6"	B92BRM2XWJ	115 vac	0.8	100%
T-57	8"	C92BRM2XWJ	115 vac	1.0	50%

SHIPS IN
24 HRS !



Series 92/Type 21 Ball Valve Standard Features (Sizes 1/2" - 4")

- UL-508 Listed electric actuator
- Type-21 PVC with EPDM or FKM seals, Tru-Union Ball Valve
- T-21 1/2" - 2" supplied with both socket and threaded ends, 2-1/2" - 4" Socket only
- 120 VAC capacitor run reversing Type Motor
- Thermal overload protection with auto reset
- De-clutchable manual override
- Visual beacon position indicator
- 10 second cycle time *
- Type 4X/7 diecast aluminum w/ powdercoat finish enclosure
- 2 End of travel limit switches
- 2 Additional limit switches for indication
- PPG mounting bracket with 304 SS coupling and hardware
- Complete factory assembled and tested actuated valve package