

# Fast Pack - Valve/Actuator Packages

SHIPS IN  
24 HRS !



## Series 94/Type 57 Butterfly Valve Standard Features (Sizes 1-1/2" - 4")

- UL-508 Listed electric actuator
- Type-57 PVC body, PP disc, EDPM or FKM seals , wafer style
- 120 VAC capacitor run reversing type motor
- Thermal overload protection with auto reset
- De-clutchable manual override
- Visual position indicator
- 5 second cycle time\*
- Mechanical brake supplied as standard for 4" T-57 butterfly valves
- Type 4X engineered resin enclosure
- 2 end of travel limit switches
- 2 Additional limit switches for indication
- Complete factory assembled and tested actuated valve package

SHIPS IN  
24 HRS !



## Series 94/Type 21 Ball Valve Standard Features (Sizes 1/2" - 4")

- UL-508 listed electric actuator
- Type-21 PVC with EPDM or FKM seals, Tru-Union Ball Valve
- T-21 1/2" - 2" supplied with both socket and threaded ends, 2-1/2" - 3" socket only
- 120 vac capacitor run reversing type motor
- Thermal overload protection with auto reset
- De-clutchable manual override
- Visual position indicator
- 5 second cycle time\*
- Type 4X engineered resin enclosure
- 2 End of travel limit switches
- 2 Additional limit switches for indication
- Complete factory assembled and tested actuated valve package

\*Cycle times approximate

Valve Type	Size	Actuation Model	Input Voltage	L.R. Amps	Duty Cycle
T-21	1/2" - 2"	A94M2WJ	115 vac	0.5	100%
T-21	2-1/2" - 3"	B94M2WJ	115 vac	0.8	75%
T-57	1-1/2" - 2"	A94M2WJ	115 vac	0.5	100%
T-57	2-1/2" - 3"	B94M2WJ	115 vac	0.8	75%
T-57	4"	B94BRM2WJ	115 vac	0.8	75%